

























**ANSI/ASME A112-19.8\_2007, 2008 addenda and VGB 2008 Compliance available drains**

Part #	Part Description	Picture	Specification	Size	Certifications
10058XXXX	Main drain sump with ABF 64 (11064) VGB- white, gray, black - Gunite		7.375" dia. Max flow rate: floor 104 GPM 2.68 ft/sec, wall 68 GPM 1.75 ft/sec	Sump sizes: 1.5"x1.5", 1.5"x2", 2"x2"	  <b>VGB 2008</b>
10052XXXX	Main drain sump, with ABF 64 (11064) VGB fiber glass/Vinyl liner		7.375" dia. Max flow rate: floor 104 GPM 2.68 ft/sec, wall 68 GPM 1.75 ft/sec	Sump sizes: 1.5"x1.5", 1.5"x2", 2"x2"	  <b>VGB 2008</b>
10064XXXX	Ring and Certified cover ABF 64 (11064) VGB white, black, light gray. dark gray, tan		7.375" dia. Max flow rate: floor 104 GPM 2.68 ft/sec, wall 68 GPM 1.75 ft/sec	Field sump	  <b>VGB 2008</b>
11064XXXX	Certified drain cover ABF 64 white, black, light gray. dark gray, tan		7.375" dia. Max flow rate: floor 104 GPM 2.68 ft/sec, wall 68 GPM 1.75 ft/sec	Replaces ABF 64 ABF 51	  <b>VGB 2008</b>
10064AXXX	High capacity Universal 11.125" dia. ABF 64A (10064A) VGB Anti Vortex retrofit with most drain covers, white, black, light gray, dark gary and tan		11.125" dia. Max. flow rate: floor 188 GPM 2.34 ft/sec wall 160 GPM 1.99 ft/sec	Most sumps and rings, Replaces ABF22DS, ABF23 ABF 64 ABF 51	  <b>VGB 2008</b>
10064ARXX	High capacity ring and cover 11.125" dia. ABF 64 A (10064A) VGB drain cover, white, black, light gray, dark gray and tan		11.125" dia. Max. flow rate: floor 188 GPM 2.34 ft/sec wall 160 GPM 1.99 ft/sec	New construction	  <b>VGB 2008</b>
10064ACXX	12"x12" RingPlate, with ABF 64A (10064A) VGB Certified drain cover		12"x12" squar Max. flow rate: floor 188 GPM 2.34 ft/sec wall 160 GPM 1.99 ft/sec	Fits inside most 12"x12" frames or can be installed with plaster	  <b>VGB 2008</b>
10064ACFXX	12"x12" Frame with RingPlate, ABF 64A (10064A) VGB Certified drain cover		11.125" dia. Max. flow rate: floor 188 GPM 2.34 ft/sec wall 160 GPM 1.99 ft/sec	Ready to install	  <b>VGB 2008</b>